

# Automatic Transfer Switch System

## ATS control module

Automatic Transfer Switch Control Module. The module features 8-Bit microprocessor control. The module is used to monitor two 3-phase AC supply. Once I# AC supply failure is detected (under voltage, over voltage, miss phase), The module Automatically transfer the switch to II# AC supply, and control generator to start.



## ATS switcher 40-3200A

YUYE series has been subjected to the class PC intelligent integration design, is provided with 0-position function, has a large separation distance between the contacts, is able to withstand extremely high impulse voltage (8KV and above), has dual-row composite contacts internally, in which the conductive contact area is twice that of the electromagnetic ATS switch and the copper bar, as it is punched into forming at one stroke, is characteristic of such advantages as compact volume, long service life and small arc.

YUYE series can be used for single phase load 100-630A and three phases load 100-3200A.

## Three Phase - Box, ATS switch, Control module, 15m cable.

No.	ATS Model	ATS Box	Rate Current (A)	4P ATS Switch Model	Control Module	Dimension (mm)	Weight (Kg)
1	ATS1-100A	ATS1	100A	YES1-100GA-100A-4P	HAT520	400×200×550	21
2	ATS2-160A	ATS2	160A	YES1-250GA-160A-4P	HAT520	600×320×750	50
3	ATS2-250A		250A	YES1-250GA-160A-4P	HAT520	600×320×750	50
4	ATS3-400A	ATS3	400A	YES1-630GA-400A-4P	HAT520	750×480×1500	108
5	ATS3-630A		630A	YES1-630GA-630A-4P	HAT520	750×480×1500	108
6	ATS4-1000A	ATS4	1000A	YES1-1600GA-1000A-4P	HAT520	850×560×1900	195
8	ATS4-1250A		1250A	YES1-1600GA-1250A-4P	HAT520	850×560×1900	195
9	ATS4-1600A		1600A	YES1-1600GA-1600A-4P	HAT520	850×560×1900	205
10	ATS5-2000A	ATS5	2000A	YES1-3200GA-2000A-4P	HAT520	1000×850×2100	354
11	ATS5-2500A		2500A	YES1-3200GA-2500A-4P	HAT520	1000×850×2100	356
12	ATS5-3200A		3200A	YES1-3200GA-3200A-4P	HAT520	1000×850×2100	360

## Single Phase - Box, ATS switch, Control module, 15m cable.

No.	ATS Model	ATS Box	Rate Current (A)	3P ATS Switch Model	Control Module	Dimension (mm)	Weight (Kg)
1	ATS1-100Am	ATS1	100A	YES1-100GA-100A-2P	HAT520	400×200×550	20
2	ATS2-160Am	ATS2	160A	YES1-250GA-160A-2P	HAT520	600×320×750	50
3	ATS2-250Am		250A	YES1-250GA-250A-2P	HAT520	600×320×750	71
4	ATS3-400Am	ATS3	400A	YES1-630GA-400A-2P	HAT520	750×480×1500	107
5	ATS3-630Am		630A	YES1-630GA-630A-2P	HAT520	750×480×1500	107